



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

CLASSIC DIFFERENTIAL OIL EP 90 GL5

Product No	7929
Issue No.	2
Issue Date	26/02/19

DESCRIPTION:

An extreme pressure differential oil SAE 90 mineral based differential oil with performance additives. This product is for use in hypoid differentials requiring extreme pressure lubricants providing superior performance.

APPLICATION:

Use as received in Hypoid differentials requiring extreme pressure lubricants and GL5 specification. For highly loaded hypoid transmissions. Also suitable in transmissions with brass & bronze components.

USER BENEFITS:

Well proven superior performance.
Provides 'trouble free' operation.
Imparts exceptional load carrying ability.

PERFORMANCE PROFILE:

Provides performance meeting or exceeding API GL5, MIL-L-2105D, OEM performance levels for final drives.

TYPICAL CHARACTERISTICS:

SAE viscosity grade	9
Specific gravity at 15°C	0.893
Kinematic viscosity at 100°C	15.4cSt
Kinematic viscosity at 40°C	153.0cSt
Viscosity index	102
Pour point °C	-18
Flashpoint °C	205

HEALTH AND SAFETY:

Health and Safety Data Sheet 7929 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk